

(54) Title of the invention : MANAGEMENT DEVICE FOR COMPUTING UNIT

(51) International classification :B33Y0030000000, G06F0003048150, G06K0007100000, G06F0003048800, G06Q0020120000

(86) International Application No :NA
Filing Date :NA

(87) International Publication No : NA

(61) Patent of Addition to Application Number :NA
Filing Date :NA

(62) Divisional to Application Number :NA
Filing Date :NA

(71)**Name of Applicant :**
1)Noida Institute of Engineering and Technology, Greater Noida
 Address of Applicant :Plot No. -19, Knowledge Park-II, Institutional Area, Greater Noida, Uttar Pradesh-201306, India. Greater Noida -----

Name of Applicant : NA
Address of Applicant : NA

(72)**Name of Inventor :**
1)Dr. Imran Ali
 Address of Applicant :Master of Business Administration, Noida Institute of Engineering and Technology, Greater Noida, Plot No. -19, Knowledge Park-II, Institutional Area, Greater Noida, Uttar Pradesh-201306, India. Greater Noida -----

2)Rahul Kumar Sharma
 Address of Applicant :Department of Computer Science and Engineering, Noida Institute of Engineering and Technology, Greater Noida, Plot No. -19, Knowledge Park-II, Institutional Area, Greater Noida, Uttar Pradesh-201306, India. Greater Noida - -----

3)Dr. Priyanka Malhotra
 Address of Applicant :Master of Business Administration, Noida Institute of Engineering and Technology, Greater Noida, Plot No. -19, Knowledge Park-II, Institutional Area, Greater Noida, Uttar Pradesh-201306, India. Greater Noida -----

(57) Abstract :
 A management device for computing unit comprises of a platform 1 configured with multiple flaps 2, 3 associated with the device, to be fixed with a surface, a first and second flaps 2, 3 attached over the platform 1 and hinged with each other to allow a user to position the computing unit over the second flap 3, an artificial intelligence based camera 4 mounted over the platform 1 to capture multiple images of surroundings to allow the user to select a surface where the user wants to fix the platform, an electromagnetic coil 8 fabricated within the second flap 3, paired with a battery installed within the platform 1 to create a magnetic field for transmitting energy to the user's computing unit to charge, a light detection sensor installed over the platform to detect intensity of display of the computing unit.

No. of Pages : 13 No. of Claims : 3